

SIMPLEX ONE-WAY WATER EYE

GVS - 380



- ▶ Waterproof Max: 30m
- ▶ 1/3" Super HAD SONY CCD*4.
- ▶ Effective Pixels : 410K.
- ▶ Super White LED.
- ▶ 6mm Lens.
- ▶ Perfect Vacuum.
- ▶ Order made Production.
- ▶ TFT LCD Monitor 14.1" KIT (Pelikan case)
- ▶ lighting On/Off

SPECIFICATION	GVS - 380
Image Sensor	Super HAD SONY 1/3" HAD CCD*4
Effective Pixels	410K
Self-Illumination	built-in, 40LED
Water Pressure	30Kg/Cm ^ 2
S/N	MORE THAN 50dB
Image Output	1.0V p-p 75 Ohm
Lens	6mm (FOV 53°)
Cable Material	Underwater urethane coaxial cable , basically 50m, (option : 100m, 200m)
Operating Temperature	-30℃~60℃
Case	Poly Urethane
Min. Illumination	0.1 LUX
Visible Range	Different according to turbidity (Max. 3~5m)
Lamp Lifetime	Max 50,000 Hour
Power Consumption	12W
Power Supply	DC 24V / 2.5A
Dimension	Ø290*150mm(Vacuum nozzle included)
Monitor KIT	14.1" Wide LCD Monitor DC 24V / 5A Battery (5~6hours recharging / 4hours continuous use available)
Weight	12Kg (Only Camera)
Remark	Design and specification of camera could be changed according to uses, water depth, density.

GVS Co.,LTd

address : #505,B-Dong, Woorim Lions Valley, 425 , Cheongcheon-Dong, Bupyeong-Gu, Incheon,
 Tel : +82-32-623-5338, Fax : +82-32-623-6388
 webpage : www.e-gvs.co.kr, E-mail : hinet007@dreamwiz.com